

IN THE SPECIFICATION

page 2:

[0007] To achieve the above-mentioned object, a golf bag of the present invention comprises a bag body, a tilting device, and a ~~support bracket~~ support. The bag body has an inner storage rack which comprises a top frame, a ~~middle~~ lower frame, a ~~bottom~~ base frame, a plurality of ~~support rod~~ frame rods provided between the top frame and the ~~middle frame~~ lower frame and a joint block for stably coupling the ~~middle~~ lower frame and the ~~bottom~~ base frame. The tilting device comprises a fixed leg tilt control body and a pair of steel wires extending therefrom, the fixed leg tilt control body having a ~~moveable shank~~ release shank therein, a notch and a retainer formed in the upper portion thereof, a protrusion formed on the upper portion of the ~~moveable shank~~ release shank and a support feet control foot formed at the lower portion thereof to push the ~~moveable shank~~ release shank to move up and down relative to the fixed leg tilt control body. The ~~middle frame~~ lower frame have a Σ-shaped frame has an engaging body which can disengage with the ~~notch~~ retainer through the push of the ~~moveable shank~~ release shank.

[0008] In the present invention, the ~~bottom frame~~ base frame has a flat bottom surface and the control foot there is a distance from the ~~support foot~~ to above a the bottom surface of the ~~bottom~~ base frame. The Σ-shaped frame engaging body comprises an upper edge retainer projection on an upper portion and a lower edge release projection on a lower portion, and the Σ-shaped frame engaging body clasps the ~~notch~~ retainer through by the upper edge retainer projection thereof. The upper edge retainer projection of the Σ-shaped frame engaging body is released from the ~~notch~~ retainer by using the ~~moveable shank~~ release shank to push the bottom edge.

[0015] Referring now to the drawings in detail, FIGS. 1-3 show a golf bag according to an embodiment of the present invention. The golf bag comprises a bag body, a ~~support bracket~~ 2, and a tilting device. The bag body comprises an inner storage rack and an outer wrappage